



RP503

TUBE CHANNEL

- Tube Mic Preamp
- Optical Compressor

• Equalizer

The Bellari RP503 is a single rack space mic preamp, compressor/limiter, and three band equalizer designed for the professional audio and home recording market. The unit is ideal for any recording situation, but proves most effective in natural, pleasant signal conditioning for the digital recording medium.

FEATURES

- · Warm, silky tube preamplification
- +48 Volt Phantom Power
- Smooth, natural optical compression
- Side Chain for direct access to the compressor's detector circuits
- Calibrated VU metering
- Three band EQ with sweepable mid section
- All tube gain circuitry with high-voltage plate voltages
- 1/4" and XLR inputs and outputs

SPECIFICATIONS

Output Impedance:

Input Impedance: 600 Ohms balanced

50K Ohms unbalanced (1/4") 50 OhmsTRS Balanced -15 dBV XLR 600 Ohms

Max Input Level: -15 dBV XLR 6 +18 dBV 1/4"

Max Gain: +65 dB

Max Output Level: +22 dB Frequency Response 20Hz - 25kHz +/-3dB

THD + Noise <0.1% typical Noise Floor - 75 dB

Equalizer Boost/Cut: +/- 15 dB

Equalizer settings:

Low shelf: 150 Hz High shelf: 10 kHz

Mid fregencies: 300 Hz - 5 kHz, Q = 1

Compressor settings:

Weight

Threshold: -30 dB to +20 dB

Ratio: 2:1 to 8:1

Indicators Phantom Power LED, Clip LED, Power LED

Analog VU Meter

Input/Output jacks XLR balanced

1/4" unbalanced

1/4" TRS unbal. Side Chain

Dimensions 1.75" x 6" x 19"

(90mm X 162mm X 482mm)

3.5 lbs. (1.75 Kg)

Power 120VAC (230VAC) 15VA



Bellari is a division of ROLLS Corporation 5968 South 350 West Salt Lake City, UT 84107