



RPQ160b

ROLLS

Parametric Equalizer



ROLLS Parametric Equalizer

LOW SHELF: High Pass Filter control; adjusts the amount of low frequency rolloff from 500 Hz down to 16Hz for the entire output of the RPQ160.
HIGH SHELF: Low Pass Filter control; adjusts the amount of high frequency rolloff from 1 kHz up to 20 kHz for the entire output of the RPQ160.

NOTE: THERE IS NO BYPASS SWITCH FOR THE LOW OR HIGH SHELF FILTERS - SIMPLY TURN THE LOW SHELF COMPLETELY COUNTERCLOCKWISE, AND THE HIGH SHELF COMPLETELY CLOCKWISE TO BYPASS THESE CIRCUITS.

LEVEL: Adjusts the overall signal level of the RPQ160.

NOTE: The following three descriptions are identical for all four bands of equalization.

FREQUENCY: Selects the frequency to be boost or cut. The band frequency ranges are listed below:

- Band 1: 70 Hz to 1.5 kHz
- Band 2: 150 Hz to 3 kHz
- Band 3: 300 Hz to 10 kHz
- Band 4: 600 Hz to 20 kHz




WIDTH: (Q): Varies the shape or width of the equalization being boost or cut from .3 to 3 octaves wide.

LEVEL: Boosts or cuts the signal of the indicated band from -15 to +15 dB.

Power Switch: Applies power to the RPQ160 when the unit is connected to a properly grounded ac outlet. The Power LED will light when the RPQ160 is on.



The High Shelf Sweep Diagram shows the response curve of the High Shelf filter at its minimum and maximum setting.



SPECIFICATIONS

CONTROLS MAIN SECTION

- Master Level: -12 to +12 dB
- Low Shelf: 16 to 500 Hz High-pass filter
- High Shelf: 1 to 30 kHz Low-pass filter
- Active Switch: Activates/bypasses equalization circuitry

CONTROLS FREQUENCY SECTIONS

- Frequency Controls: 70Hz to 1.5kHz
150Hz to 3kHz
300Hz to 10kHz
600Hz to 20kHz
- Width: .3 to 3 Octaves each band
- Level: -15 to +15 dB each band

- Frequency Response: 16 Hz to 30 kHz +/-3 dB
- THD: <.03%
- S/N Ratio: >90 dB
- Max Input: +22 dB
- Max Output: +22 dB
- Input Impedance: 10KΩ (20K balanced)
- Output Impedance: 50Ω
- Shelving Slope: 12 dB / Octave
- Size: 19" x 4" x 1.75"

Weight: 4 lbs.

XLR, RCA AND 1/4" INPUTS

XLR, RCA AND 1/4" OUTPUTS

ROLLS

5968 SOUTH 350 WEST S.L.C., UT 84107

PHONE: 801-263-9053

FAX: 801-236-9068

MADE IN USA

